



NOTES

1. *BROKEN LINES REPRESENT NORMAL CONNEXIONS, FULL LINES NEW OR ALTERED CONNEXIONS.*
2. *RING AND SPEAK KEYS, ALSO RING BACK AND DIAL KEYS, WILL BE COMBINED.*
3. *RING AND RING BACK KEYS WILL BE ACTUATED BY MOVEMENT OF HANDLES TOWARDS OPERATOR.*
4. *KEYS AND PLUGS WILL BE LABELLED AS SHOWN.*
5. *THE MINIMUM P. D. WILL BE DETERMINED BY CONSIDERATION OF THE TRANSMISSION OR SIGNALLING REQUIREMENTS OF EACH INDIVIDUAL CASE.*
6. *APPARATUS THROWN OUT OF USE WILL BE RECOVERED UNLESS A REVERSION TO STANDARD ARRANGEMENTS IS CONTEMPLATED. INDICATORS 600A WILL BE REPLACED BY INDICATORS 600C.*
7. *NIGHT SERVICE WILL BE PROVIDED BY SEPARATE DOUBLE-PLUGGED CORDS.*
8. *THE EXCHANGE LINES MUST BE REVERSED IN ALL CASES.*
9. *THE DIAL KEY AND DIAL CIRCUIT TO BE FITTED IN AUTOMATIC AREAS ONLY.*

APPARATUS	RATE BOOK DESCRIPTION
A & B	INDICATOR No. 600 C.
QA	CONDENSERS M.C. No. 30.
YA	RESISTOR SPOOL No. 1-100Ω.
SPEAK & RING KEY	KEY No. 204.
RING BACK & DIAL KEY	KEY No. 219.
S	RELAY No. 22L.