

REFERENCES:-

PRIMARY SURGE PROTECTION TI C3 FO052

			CARUTISM TELECOMBUNICATIONS 1981		
BRITISH TELECOMMS HQRS			-15 de 1		
PAPER:- W	ISSUE		1 (1.1) (1.1 2 7, (1.1 (1.1) (1.1)		
DISTRIBUTION:- GENERAL		7	SHP OF Colin Dellation	ME/PD 1.1.1.	23-10-81

NOTES :-

- I. TELEPHONE No. 8786 IS A 12 BUTTON, MF4 SIGNALLING PRESS-BUTTON TELEPHONE, INTENDED FOR USE ON SUITABLY EQUIPPED PSTN LOCAL EXCHANGE LINES AND PBX's.
- 2. THE TELEPHONE No. 8786 IS FITTED WITH A RESISTOR IN SERIES WITH THE TONE CALLER AND IS INTENDED FOR PARALLEL WORKING USING LINE JACK UNIT..., OR JACK No. 620 SERIES.
- 3. LINE JACK UNIT ... / IA, 2A OR 3A SHOULD BE USED AS APPROPRIATE. FOR PBX EXTERNAL EXTENSIONS A LINE JACK UNIT ... / IA SHOULD BE USED IF PRIMARY SURGE PROTECTION IS REQUIRED AS DEFINED IN TICS FOOSE SECTION 4.
- 4. ON SOME REFURBISHED PRESS-BUTTON TELEPHONES, TERMINALS 16,17 & 18 DO NOT EXIST. THEY HAVE BEEN REDESIGNATED AS TERMINALS 2A,19B & 19A RESPECTIVELY. THE BELL WILL BE CONNECTED BETWEEN TERMINALS T4 & T19,NOT BETWEEN TERMINALS T4 & T16 AS SHOWN. THE WHITE CONDUCTOR OF THE CORD CONNECTING No. 4/504 WILL BE CONNECTED TO T19 AND NOT T18 AS SHOWN.

