## CIRCULATION Suffix MINOR AMENDMENTS Amendt ₹

## H.E.S. No.3.(KEYMASTER) EXCHANGE SERVICE BARRED RELAY-UNIT Q 408

Q(L)408

## INSTALLATION NOTES

- RELAY UNIT IS FITTED INSIDE TELE, INTERCOM. No.3/I AT BARRED STATION AND MOUNTED ON RIGHT-HAND SIDE BELL-GONG (NEWED FROM FRONT OF TELEPHONE) REMOVE GONG FIXING SCREW, PLACE UNIT OVER GONG AND REPLACE SCREW
- 2. FLEXIBLE LEADS TO BE TAKEN TO REAR OF TELEPHONE AND TERMINATED AS SHOWN IN PANEL 3. THE LEADS MUST BE SECURED TO PREVENT INTERFERENCE WITH BELLEGONGS AND GRAVITY-SWITCH
- STRAP BETWEEN TIG-TIT TO BE REMOVED
- THE OR AND BLU CONDUCTORS TO BE SHIFTED FROM EXISTING TERMINALS 29 AND 27 TO SPARE TERMINALS TIL AND TI2
- 5. THE BRN-SL CONDUCTOR TO BE SHIFTED FROM 25 TO TI3 (SPARE)

SCHEMATIC

## RELAY UNIT Q 408 INCLUDES RELAY No. 16/1 (RELAY BR)



