

H.E.S. No.4

NON-MULTIPLE EXTENSION
 PLAN IA (INTERNAL ONLY)
 USING TELEPHONE No.710...

P.O. TELECOMMS. HQRS. PAPER:- W CIRCULATION:- GENERAL	ISSUE		
		A T6 CONNEXIONS REPLACED BY STRAPS T6-T7 <i>[Signature]</i> (51/3) TDI.4.	5.2.68. 15-2-66

Q553
PAGE 2-3
ISSUE A


NOTES :-

1. THE FACILITIES OF PLAN 1A ARE SHOWN ON DGM. N1425
2. APPARATUS REQUIRED :-
 MAIN
 TELEPHONE NO. 710...
 1 PART 22/DBU/260
 1 PART 23/DBU/260
 1 PART 1/DPL/378
 1 PART 1/DPL/379
 1 BLOCK TERMINAL NO. 35A
 1 THERMISTOR NO. 1A-1 (MAIN ONLY)
 1 CORD INSTRUMENT NO. 4/83AA...
 2 SWITCHES NO. 5A-4


 INTERMEDIATE
 ITEMS AS MAIN PLUS
 1 PART 3/DBU/262
 1 CORD INSTRUMENT NO. 5/37AA... INSTEAD OF 4/83AA...
 1 SWITCH 5A-4
 ..

 LAST
 ITEMS AS MAIN PLUS
 1 PART 3/DBU/262
 1 SWITCH 5A-4
 ..
3. REARRANGE STRAPS ON TELES. AND BLOCKS TERMINAL AS SHOWN.
4. WHEN EXTN. BELL IS REQUIRED CONNECT IN PLACE OF STRAP BT3-9. TOTAL NUMBER OF BELLS, INCLUDING BELLS IN TELEPHONES, MUST NOT EXCEED THREE.
5. A MAXIMUM OF TWO EXTENSIONS, THREE TELEPHONES NO.710 IN ALL, MAY BE PROVIDED.
6. AT MAIN AND EXTENSION TELE.NO.710... REMOVE PLUNGERS FROM POSITIONS B AND C AND FIT SWITCH 5A-4 WITH PART 1-DPL/379 IN POSITION B. FIT SWITCH 5A-4 AND PART 1/DPL/378 IN POSITION C.
 AT EXTENSION TELE.NO.710... FIT SWITCH 5A-4 IN POSITION A.
 IN TELEPHONE COVER FIT PART 22/DBU/260 IN POSITION B, FIT PART 23/DBU/260 IN POSITION C,
 FIT PART 3/DBU/262 IN POSITION A.

EXCH. EXTN.



LATCHING BRACKET



7. EXTENSION SWITCH (LOCKING) OPERATES SINGLY RETURNING LOOP TO MAIN STATION. EXCHANGE SWITCH (NON LOCKING) ALSO OPERATES EXTENSION SWITCH CONTACTS PROVIDING EARTHED LOOP CALLING TO SWITCH RELAY UNIT Q519
8. ANY SPARE LEADS SHOULD BE SECURED ON SPARE TERMINALS OR ELECTRICALLY INSULATED.

